



ABB Stmívač 6523 UR-104-500 Příklad univerzální i LED žárovky 2CKA006512A0354

» Domovní vypínače a zásuvky » ABB » Příklad » Spínače, strojky » Stmívače



Kód produktu 36565

EAN 4011395344071

Příklad stmívače univerzální i LED žárovky. Tlačítkové spínání a otočné ovládání (typ 6523 UR-104-500)

Dostupnost na hlavním skladě: na objednávku

ABB Stmívač 6523 UR-104-500 Přístroj univerzální i LED žárovky 2CKA006512A0354

» Domovní vypínače a zásuvky » ABB » Přístroje » Spínače, strojky » Stmívače

Popis

LED dimmer With rotary control.
Two-way switch and soft-catch.
With N-terminal.
2- or 3-wire connection (neutral conductor not required).
Neutral conductor optionally connectable
(recommended for the connection of low loads < 10 W/VA).
Very low installation depth: < 20 mm Without claws.
Optimised for dimming of retrofit LED lamps (LEDi).
For dimmable Retrofit-LEDs (LEDi).
For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.
For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps.
Mix operation of LEDi with conventional loads possible.
With manually adjustable operating mode: trailing / leading edge control.
With adjustable minimum/maximum brightness.
Low-noise level by MOSFET transistors.
With electronic short-circuit protection. With electronic overload protection.
Without cover plate.
Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz
Nominal power (L): 2 - 100 W/VA (leading-edge control)
Nominal power (R, C): 10 - 360 W/VA (trailing-edge control)
Nominal power (LEDi): 2 - 100 W/VA (leading-edge control)
Nominal power (LEDi): 2 - 200 W/VA (trailing-edge control)

Soubory ke stažení

[abb-logo.svg \(1.26kB\)](#)