



ABB Stmívač 6523 UR-104-500 Příklad univerzální i LED žárovky 2CKA006512A0354

» Domovní vypínače a zásuvky » ABB » Příklad » Spínače, strojky » Stmívače



Kód produktu 36565

EAN 4011395344071

Příklad stmívače univerzální i LED žárovky. Tlačítkové spínání a otočné ovládání (typ 6523 UR-104-500)

Dostupnost na hlavním skladě: na objednávku

ABB Stmívač 6523 UR-104-500 Přístroj univerzální i LED žárovky 2CKA006512A0354

» Domovní vypínače a zásuvky » ABB » Přístroje » Spínače, strojky » Stmívače

Popis

LED dimmer With rotary control.

Two-way switch and soft-catch.

With N-terminal.

2- or 3-wire connection (neutral conductor not required).

Neutral conductor optionally connectable

(recommended for the connection of low

loads < 10 W/VA).

Very low installation depth: < 20 mm Without claws.

Optimised for dimming of retrofit LED lamps (LEDi).

For dimmable Retrofit-LEDs (LEDi).

For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.

For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps

with conventional or electronic transformers and

dimnable energy-saving halogen

lamps.

Mix operaton of LEDi with conventional loads possible.

With manually adjustable operating mode: trailing / leading edge control.

With adjustable minimum/maximum brightness.

Low-noise level by MOSFET transistors.

With electronic short-circuit protection. With electronic overload protection.

Without cover plate.

Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz

Nominal power (L): 2 - 100 W/VA (leading-edge control)

Nominal power (R, C): 10 - 360 W/VA (trailing-edge control)

Nominal power (LEDi): 2 - 100 W/VA (leading-edge control)

Nominal power (LEDi): 2 - 200 W/VA (trailing-edge control)

Soubory ke stažení

[abb-logo.svg \(1.26kB\)](#)